

## ! SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Name of product** All-purpose cleaner  
Code-Nr. 100 741

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Recommended intended purpose(s)

Technical Aerosols

### 1.3. Details of the supplier of the safety data sheet

#### Distributor

LAMPERT Werktechnik GmbH  
Ettlebener Str. 27, 97440 Werneck  
Tel.: 09722 9459 0, Fax: 09722 9459 100  
Mail: mail@lampert.info, Web: www.lampert.info

#### Advice

LAMPERT Werktechnik GmbH  
Ettlebener Str. 27, 97440 Werneck  
Tel.: 09722 9459 0, Fax: 09722 9459 100  
Mail: mail@lampert.info, Web: www.lampert.info

### 1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:  
++44 1865 407333 (English)  
TRANSPORT EMERGENCY CONTACT - UK, UAE, South  
Africa (24h): Tel: ++44 1865 407333 (English)

#### Manufacturer

WEICON GmbH & Co. KG  
Königsberger Str. 255, DE-48157 Münster

### 1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):  
Tel: ++49 69 222 25285 (Deutsch, Englisch)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Aerosol 1	H222, H229
Skin Irrit. 2	H315
STOT SE 3	H336
Aquatic Chronic 2	H411

#### Hazard Statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

## 2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS02



GHS07



GHS09

### Signal word

Danger

### Hazard Statements

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

### Precautionary Statements

P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264 Wash hands thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 Call a POISON CENTER or doctor/physician if you feel unwell.  
P332 + P313 If skin irritation occurs: Get medical advice/attention.  
P362 Take off contaminated clothing.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
P501 Dispose of contents/container to hazardous or special waste collection point.

### 2.3. Other hazards

Product has an anesthetic effect.

### Information pertaining to special dangers for human and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

### Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.



## SECTION 3: Composition/ information on ingredients

### 3.1. Substances

not applicable

### 3.2. Mixtures

#### Description

Mixture of active ingredients with propellant

#### Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
64-17-5	200-578-6	ethanol	3 - 9,9	Flam. Liq. 2, H225
106-97-8	203-448-7	butane	3 - 9,9	Flam. Gas 1, H220 / Press. Gas
109-66-0	203-692-4	pentane	10 - 24,9	Flam. Liq. 2, H225 / Asp. Tox. 1, H304 / STOT SE 3, H336 / Aquatic Chronic 2, H411
74-98-6	200-827-9	propane	3 - 9,9	Flam. Gas 1, H220 / Press. Gas
64742-49-0	921-024-6	Naphtha (petroleum), hydrotreated light	50 - 74,99	Flam. Liq. 2, H225 / Asp. Tox. 1, H304 / Aquatic Chronic 2, H411 / Skin Irrit. 2, H315 / STOT SE 3, H336

#### REACH

CAS No	Name	REACH registration number
74-98-6	propane	01-2119486944-21
64742-49-0	Naphtha (petroleum), hydrotreated light	01-2119475514-35

#### Labelling for contents according to regulation (EC) No 648/2004, annex VII

30 % and more aliphatic hydrocarbons

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Remove contaminated soaked clothing immediately.

#### In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

#### In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

#### In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

#### In case of ingestion

Do not induce vomiting.

If swallowed seek medical advice immediately and show the doctor packing or label.

### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

No information available.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Alcohol-resistant foam  
Dry powder  
Carbon dioxide  
water mist

#### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

Danger of bursting  
In case of fire formation of dangerous gases possible.

### 5.3. Advice for firefighters

#### Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

#### Additional information

Cool endangered containers with water spray jet.  
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

---

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Ensure adequate ventilation.  
Use personal protective clothing.

### 6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.  
Do not discharge into the drains or bodies of water.  
Do not discharge into the drains/surface waters/groundwater.

### 6.3. Methods and material for containment and cleaning up

Allow to vaporise.

#### Additional Information

Sort out leaky cans and dispose according to regulations.

### 6.4. Reference to other sections

Safe handling: see section 7  
Disposal: see section 13  
Personal protection equipment: see section 8

---

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

#### General protective measures

Avoid contact with eyes and skin  
Do not inhale gases/vapours/aerosols.

---



**Hygiene measures**

At work do not eat, drink and smoke.  
 Wash hands before breaks and after work.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking  
 Do not spray on a naked flame or any incandescent material.  
 Protect from heat and sunlight.  
 Vapours can form an explosive mixture with air.  
 Take precautionary measures against static discharges.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

**Advice on storage compatibility**

Do not store together with food.

**Further information on storage conditions**

keep dry and cool. The local authorities' regulations relating to the storage of compressed gas packagings (aerosol cans) must be adhered to.  
 Protect from heat and direct solar radiation.  
 Keep container in a well-ventilated place  
 Storage temperature may not exceed 50°C (=122°F).  
 Recommended storage temperature: room temperature.

**7.3. Specific end use(s)**

**Recommendation(s) for intended use**

See section 1.2

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
106-97-8	Butane	8 hours	1450	600	EH40/2005
		Short-term	1810	750	
64-17-5	ethanol	8 hours	1920	1000	EH40/2005

**Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)**

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
109-66-0	pentane	8 hours	3000	1000	

**DNEL-/PNEC-values**

**DNEL worker**

CAS No	Substance name	Value	Code	Remark
64-17-5	ethanol	343 mg/kg	DNEL long-term dermal (systemic)	
		950 mg/m3	DNEL acute inhalative (systemic)	
		1900 mg/m3	DNEL acute inhalative (local)	
64742-49-0	Naphtha (petroleum), hydrotreated light	2035 mg/m3	DNEL long-term inhalative (systemic)	
		773 mg/kg bw/day	DNEL long-term dermal (systemic)	

**DNEL Consumer**

CAS No	Substance name	Value	Code	Remark
64742-49-0	Naphtha (petroleum), hydrotreated light	608 mg/m <sup>3</sup>	DNEL long-term inhalative (systemic)	
		699 mg/kg bw/day	DNEL long-term oral (repeated)	
		699 mg/kg bw/day	DNEL long-term dermal (systemic)	

**Additional advice**

The statutory local and national regulations have to be observed.

**8.2. Exposure controls**

**Respiratory protection**

If ventilation insufficient, wear respiratory protection.

Short-term: filter apparatus, filter AX, otherwise environment-independent breathing apparatus.

**Hand protection**

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification: Nitrile rubber

**Eye protection**

lightly fitting goggles

**Other protection measures**

protective clothing

**Appropriate engineering controls**

Sufficient ventilation and exhaustion.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**Appearance**

aerosol

**Colour**

colourless

**Odour**

characteristic

**Odour threshold**

not determined

**Important health, safety and environmental information**

	Value	Temperature	at	Method	Remark
<b>pH value</b>	not determined				
<b>boiling point</b>	not applicable				
<b>Melting point / Freezing point</b>	not determined				
<b>Flash point</b>	not applicable				Aerosol
<b>Vapourisation rate</b>	not determined				

	Value	Temperature	at	Method	Remark
<b>Flammable (solid)</b>	not determined				
<b>Flammability (gas)</b>	not determined				
<b>Ignition temperature</b>	200 °C				
<b>Self ignition temperature</b>					The product is not self-igniting.
<b>Lower explosion limit</b>	0,8 Vol-%				
<b>Upper explosion limit</b>	15 Vol-%				
<b>Vapour pressure</b>	573 hPa	20 °C			
<b>Relative density</b>	0,669 g/cm <sup>3</sup>	20 °C			
<b>Vapour density</b>	not determined				
<b>Solubility in water</b>	5 g/l	20 °C			
<b>Solubility/other</b>	not determined				
<b>Partition coefficient n-octanol/water (log P O/W)</b>	not determined				
<b>Decomposition temperature</b>	not determined				
<b>Viscosity</b>	not determined				
<b>Solvent content</b>	100 %				

**Oxidising properties**

No information available.

**Explosive properties**

The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .

**9.2. Other information**

No information available.

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

No information available.

**10.2. Chemical stability**

No information available.

**10.3. Possibility of hazardous reactions**

No information available.

**10.4. Conditions to avoid**

Keep away from heat.



### 10.5. Incompatible materials

No information available.

### 10.6. Hazardous decomposition products

No hazardous decomposition products known.

### Thermal decomposition

Remark No decomposition if used as directed.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
<b>LD50 acute oral</b>	> 5840 mg/kg	rat		Information concerns to main component.
<b>LD50 acute dermal</b>	> 2920 mg/kg	rabbit		Informations concern to main component.
<b>LC50 acute inhalation</b>	> 25 mg/l (4 h)	rat		Informations concern to main component.
<b>Skin irritation</b>	irritant			
<b>Eye irritation</b>	non-irritant			
<b>Skin sensitization</b>	non-sensitizing			

#### Experiences made from practice

Irritates respiratory tract.

Irritates mucous membranes.

Inhalation causes narcotic effect/intoxication.

#### Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### Ecotoxicological effects

	Value	Species	Method	Validation
<b>Fish</b>	LC50 4,26 mg/l (96 h)	Oncorhynchus mykiss		Pentane
<b>Daphnia</b>	EC50 3 mg/l (48 h)	Daphnia magna		Information refers to the main component.
<b>Algae</b>	NOEC 7,51 mg/l (72 h)	Pseudokirchneriella subcapitata		Pentane

### 12.2. Persistence and degradability



No information available.

**12.3. Bioaccumulative potential**

No information available.

**12.4. Mobility in soil**

No information available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Other adverse effects**

**General regulation**

Even in the event of low quantities penetration into the underground drinking water is contaminated.

Toxic to fishes.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.

Harmful to fishes and bacteria.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Waste code No.**

15 01 10\*

**Name of waste**

packaging containing residues of or contaminated by hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

**Recommendations for the product**

Remove in accordance with local official regulations.

**Recommendations for packaging**

Dispose of according to the local waste regulations.

**General information**

For proper waste disposal a complete emptying of the tin is necessary.

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

**SECTION 14: Transport information**

	ADR/RID	IMDG	IATA-DGR
<b>14.1. UN number</b>	1950	1950	1950
<b>14.2. UN proper shipping name</b>	AEROSOLS (Naphtha (petroleum), hydrotreated light)	AEROSOLS (Naphtha (petroleum), hydrotreated light)	Aerosols, flammable (Naphtha (petroleum), hydrotreated light)
<b>14.3. Transport hazard class(es)</b>	2.1	2.1	2.1
<b>14.4. Packing group</b>	-	-	-
<b>14.5. Environmental hazards</b>	Yes	Yes	Yes

**14.6. Special precautions for user**

Caution: Gases

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**  
not applicable

**Land and inland navigation transport ADR/RID**

Hazard label(s) 2.1  
tunnel restriction code D  
Classification code 5F  
transport in "limited quantities" according to 3.4 ADR is possible

**Marine transport IMDG**

MARINE POLLUTANT

## SECTION 15: Regulatory information

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**VOC standard**

VOC content 100 %

VOC value 669 g/L

**15.2. Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

**Recommended uses and restrictions**

National and local regulations concerning chemicals shall be observed.

For industrial use only.

**Further information**

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! — Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.4

H220 Extremely flammable gas.  
H225 Highly flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.